


MODEL KAW1060
50 WATTS CW
400 MHz - 1000 MHz

The Model KAW1060 is a Class A wideband RF power amplifier delivering in excess of 50 Watts CW power into a 50-Ohm load over the frequency range of 400 MHz to 1000 MHz. Power gain is a minimum of 47 dB. GPIB control requires the optional IEEE488.2/RS232 Interface Controller Module.

The system features forward and reflected power indication on a front panel-mounted, analog meter; Automatic Level Control (ALC); RF gain control; overdrive protection; full VSWR protection; input blanking, and over-temperature protection. On the basic model these features, plus remote power on/off control, are accessible for hard-wire remote operation through a 25-pin, D-subminiature connector. For a detailed description of these features refer to "SPECIAL FEATURES – KAA & KAW-SERIES SINGLE BAND RF POWER AMPLIFIERS".

The Model KAW1060 is a 19-inch rack-mount unit, 7 inches high and 18 inches deep. Construction is completely modular; all subassemblies are readily removable. Forced-air cooling is by a highly reliable, tube-axial fan mounted on the rear panel. The amplifier operates from 95-132 or 187-265 V_{AC}, 47-63 Hz line. The system may be placed in 'stand-by' mode with the BLANKING switch, which greatly reduces energy consumption and heat generation.



SPECIFICATIONS
Model KAW1060

RATED POWER OUTPUT	50 Watts
INPUT FOR RATED OUTPUT	1.0 mW maximum
POWER OUTPUT @ 1dB COMPRESSION	50 Watts minimum
FLATNESS	± 1.5 dB maximum unleveled, ± 0.5 dB leveled
FREQUENCY RESPONSE	400 MHz - 1000 MHz instantaneously
GAIN	47 dB minimum
GAIN ADJUSTMENT RANGE	20 dB typical
INPUT IMPEDANCE	50 Ohm nominal
OUTPUT IMPEDANCE	50 Ohm nominal
MISMATCH TOLERANCE	infinite
PROTECTION	VSWR, over-temperature, overdrive
MODULATION CAPABILITY	Will faithfully reproduce AM, FM, or pulse modulation appearing on the input signal
HARMONIC DISTORTION	-25 dBc maximum
SPURIOUS OUTPUTS	-70 dBc maximum
FRONT PANEL METER	0 - 50 Watt forward power, top scale % limit SET point reflected power, bottom scale
CONTROLS	[AC LINE]ON/OFF, [RF CTRL]ON/OFF (blanking) [METER]FLWD/REFL, [ALC]FAST/SLOW (Autom. Level Control) [VSWR]RESET MAN/AUTO, ALC, RF GAIN
INDICATORS	SYSTEM, BLANKING, [METER]MODE, [ALC] MODE, VSWR, TEMP, REMOTE ACTIVE
REMOTE INTERFACE (optional)	IEEE-488.2 & RS-232
RF CONNECTORS	Type N female
REMOTE CONTROL	IEEE488.2: 24-pin female, RS-232: 25-pin D-Subminiature female
REMOTE INTERLOCK	BNC female
OPERATING TEMPERATURE	-10 to 40 °C
COOLING	Forced air (self contained fans)
PRIMARY POWER	95 - 265 V _r , 47 - 63Hz, single-phase, 400 VA maximum
SIZE (W x H x D)	48.3 x 17.8 x 45.7 cm, 19 x 7 x 18 in.
WEIGHT	11.8 kg, 26 lb.

MODEL CONFIGURATIONS

MODEL NUMBER	OPTION
KAW1060	Standard
KAW1060M1	IEEE488.2/RS232
KAW1060M2	CW/Pulse