

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

## **MODEL 4042**

2 - 30 MHz 500 WATTS LINEAR POWER RF AMPLIFIER

## Solid State Band-specific High Power RF Amplifier

The 4042 is a 500 Watt band-specific amplifier that covers the 2 – 30 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 4042 comes with an extended multiyear warranty.

	<u>Parameter</u>	Specification @ 25 °C
<u>Electrical</u>		
1	Frequency Range	2 – 30 MHz
2	Saturated Output Power	500 Watts typical
3	Power Output @ 1dB Comp.	300 Watts min
5	Small Signal Gain	+57 dB min
6	Small Signal Gain Flatness	± 2.0 dB max
7	IP <sub>3</sub>	+61 dBm typical
8	Input VSWR	2:1 max
9	Harmonics	-15 dBc typical @ 300 Watts
10	Spurious Signals	> -60 dBc typical @ 300 Watts
11	Input/Output Impedance	50 Ohms nominal
12	AC Input Power	1800 Watts max
13	AC Input	100 – 240 VAC, single phase
14	RF Input	0 dBm max.
15	RF Input Signal Format	CW/AM/FM/PM/Pulse
16	Class of Operation	AB
<u>Mechanical</u>		
17	Dimensions	19" x 7.0" x 20"
18	Weight	60 lb. max
19	Connectors	Type-N
20	Grounding	Chassis
21	Cooling	Internal Forced Air
<u>Environmental</u>		
22	Operating Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	Normal Truck Transport
		Specifications subject to change without notice.

## **CIRCUIT PROTECTIONS**

- ♦ Thermal Overload
- ♦ Over Current
- ♦ Over Voltage

## **ORDERING MODELS**

- ♦ R Rear Panel Connectors
- ◊ F Front Panel Connectors
- ♦ RE R model w/Control Option
- ♦ FE F model w/Control Option
- ♦ RT RE model w/Ethernet Interface
- ♦ FT FE model w/Ethernet Interface



**FE Model Shown** 

Date:

Approved By: