



GLOBAL SPECIALTIES
INSTRUMENTS



Model Pro-61

Unique 5-in-1, Auto Ranging DMM, measures Volts, Amps, Temperature, Relative Humidity, dB and Lux.



Model Pro-61

- 4000 Count Blue Backlit Display
- CAT III 600V
- Auto & Manual Range
- Relative, Data Hold
- Capacitance, Temperature & Frequency ranges
- Humidity, Light & Sound measuring ranges
- Audible Continuity & Diode test
- Auto Power Off
- Rubber molded into case
- Cloth Carrying Case Included

Technical Specifications

DCV: 400m-4-40-400-600V $\pm 7\%$ of rdg + 2 digits

ACV: 4-40-400-600V $\pm 8\%$ of rdg + 3 digits

DCA: 40mA - 400mA $\pm 1.2\%$ of rdg + 3 digits, 10A $\pm 2\%$ of rdg + 10 digits

ACA: 40mA - 400mA $\pm 1.5\%$ of rdg + 5 digits, 10A $\pm 3\%$ of rdg + 10 digits

OHM: 400-4K-40K-400K-4M $\pm 1.2\%$ of rdg + 2 digits, 40M $\pm 2\%$ of rdg + 5 digits

CAP: 4nF-40nF, 400nf, 4uF 40uF-200uF $\pm 3\%$ of rdg + 3 digits

FREQ: 9.999Hz $\pm 2\%$ of rdg + 5 digits, 99.99-999.9Hz $\pm 1.5\%$ of rdg + 5 digits
99.99-199.9KHz $\pm 2\%$ of rdg + 5 digits

TEMP: Degrees C -20-0-20-400-1000 $\pm 5\%$ of rdg + 8 digits

Humidity: 30-90% $\pm 5.0\%$ RH

Sound Level: 30-100db $\pm 3.5\%$ db at 94db & 1KHz sine wave

Illumination: "Lux (4000), x 10 Lux (40000) $\pm 5\%$ of rdg + 10 digits

Audible continuity: < 40 Ohms

Power: 9 Volt NEDA 1604 or 6F22

Dimensions: 6.2" (L) x 3.0" (W) 1.5" (D)

Weight: .52 lbs.