

Table 1-1. Specifications and General Information.

**FREQUENCY****Range:**

Model 3336A:	75 ohm unbalanced	10 Hz to 20.999 999 999 MHz
	150 ohm balanced	10 kHz to 2.099 999 999 MHz
	600 ohm balanced	200 Hz to 109.999 999 kHz
Model 3336B:	75 ohm unbalanced	10 Hz to 20.999 999 999 MHz
	124 ohm balanced	10 kHz to 10.999 999 999 MHz
	135 ohm balanced	10 kHz to 2.099 999 999 MHz
	600 ohm balanced	200 Hz to 109.999 999 kHz
Model 3336C:	50 ohm unbalanced	10 Hz to 20.999 999 999 MHz
	75 ohm unbalanced	10 Hz to 20.999 999 999 MHz

**Resolution:**

- 1  $\mu$ Hz for frequencies < 100 kHz  
 1 MHz for frequencies  $\geq$  100 kHz

**Accuracy:** (instruments without Option 004)

- $\pm 5 \times 10^{-6}$  of programmed frequency

**Aging Rate:** (instruments without Option 004)

- $\pm 5 \times 10^{-6}$  per year (20° to 30°C)

**Warm-Up Time:**

- 30 minutes

**AMPLITUDE****Range:**

Model 3336A:	75 ohm output	-72.99 to +7.00 dBm
	150 ohm output	-78.23 to +1.76 dBm
	600 ohm output	-72.99 to +7.00 dBm
Model 3336B:	75 ohm output	-72.99 to +7.00 dBm
	124 ohm output	-78.23 to +1.76 dBm
	135 ohm output	-78.23 to +1.76 dBm
	600 ohm output	-72.99 to +7.00 dBm
Model 3336C:	50 ohm output	-71.23 to +8.76 dBm
	75 ohm output	-72.99 to +7.00 dBm

**Absolute Accuracy:** specified at 10 kHz for the 50, 75 and 600 ohm outputs; specified at 50 kHz for the 124, 135 and 150 ohm outputs.

- $\pm .05$  dB, for the top 9.99 dB of amplitude range (20° to 30°C)

- $\pm .08$  dB, for the top 9.99 dB of amplitude range (0° to 55°C)

**Flatness:** referenced to amplitudes at 10 kHz for the 50, 75 and 600 ohm outputs; referenced to amplitudes at 50 kHz for the 124, 135 and 150 ohm outputs.

Model 3336A	10	200	10K	50K	109K	2.09M	20.9M	
75 ohm output	± .1 dB (± .07 dB with Option 005)							
150 ohm output	± .12 dB							
600 ohm output	± .25 dB							
Model 3336B	10	200	10K	50K	109K	2.09M	10.9M	20.9M
75 ohm output	± .1 dB (± .07 dB with Option 005)							
124 ohm output	± .15 dB ± .1 dB							
135 ohm output	± .12 dB							
600 ohm output	± .25 dB							
Model 3336C	10						20.9M	
50 and 75 ohm outputs	± .1 dB (± .07 dB with Option 005)							

**Table 1-1. Specifications and General Information (Cont'd).****Attenuator Accuracy:** (instruments without Option 005)

Attenuation	10Hz	1 MHz	10M	20.9M
10 to 19.99 dB	$\pm .1$ dB	$\pm .15$ dB	$\pm .2$ dB	
20 to 39.99 dB	$\pm .15$ dB	$\pm .2$ dB	$\pm .25$ dB	
40 to 79.99 dB	$\pm .2$ dB	$\pm .25$ dB	$\pm .3$ dB	

**NOTE**

*Amplitude Accuracy is the sum of Absolute Accuracy and, as needed, Flatness and Attenuator Accuracy.*

**Warm-Up Time:**

30 minutes

**MAIN SIGNAL OUTPUTS****On Carrier Return Loss:**

Model 3336A	10	10K	30K	2.09M	10.9M	20.9M
75 ohm output	> 30 dB					
150 ohm output		> 20 dB	> 30 dB			
Model 3336B	10	10K	30K	2.09M	10.9M	20.9M
75 ohm output	> 30 dB					
124 ohm output		> 20 dB	> 30 dB			
135 ohm output		> 20 dB	> 30 dB			
Model 3336C	10	10K	30K	2.09M	10.0M	20.9M
50 ohm output		> 30 dB				> 25 dB*
75 ohm output		> 30 dB				

\* Return Loss of 50 ohm output is > 30 dB to 20.9 MHz with Option 005.

**Balance:**

Model 3336A	300	10K	50 K	2.09M	10.8M
150 ohm output		> 36 dB			
600 ohm output		> 38 dB			
Model 3336B	300	10K	50K	2.09M	10.9M
124 ohm output		> 30 dB			
135 ohm output		> 36 dB			
600 ohm output		> 38 dB			

**SPECTRAL PURITY****Integrated Phase Noise:**

Model 3336A and 3336B  
> -64 dB, for a 3 kHz band, 2 kHz either side of a 20 MHz carrier.

Model 3336C  
> -54 dB, for a 30 kHz band, centered on a 20 MHz carrier, excluding 1 Hz about the carrier.

**Phase Jitter**

.3° peak to peak maximum, measured per Bell System Technical Reference PUB 41009, "Transmission Parameters Affecting Voiceband Data Transmission—Measuring Techniques May 1975" and per CCITT Orange Book, Volume IV.2 "Specifications of Measuring Equipment".

**Table 1-1. Specifications and General Information (Cont'd).****Harmonic Distortion**

No harmonically related signal will exceed these values with respect to the carrier:

10	30	50	10K	100K	1M	5M	20.9M	
-35dB	-50dB			-60dB		-55dB	-50dB	Normal Leveling
			-50dB	-60dB	-55dB	-50dB		Fast Leveling

**Spurious:** (dc to 200 MHz except where noted)

All non-harmonically related signals from dc to 200 MHz will be more than 70 dB below the carrier or less than one of the following levels, whichever is greater.

Model 3336A	without Option 005	with Option 005
75 ohm output	-100 dBm	-115 dBm
150 ohm output	-100 dBm (to 10 MHz)	-100 dBm (to 10 MHz)
600 ohm output*	-100 dBm (to 10 MHz)	-100 dBm (to 10 MHz)
Model 3336B	without Option 005	with Option 005
75 ohm output	-100 dBm	-115 dBm
124 ohm output	-100 dBm	-115 dBm
135 ohm output	-100 dBm	-115 dBm
600 ohm output*	-100 dBm	-115 dBm
Model 3336C	without Option 005	with Option 005
50 ohm output	-100 dBm	-115 dBm
75 ohm output	-100 dBm	-115 dBm

\*Line related signals from the 600 ohm outputs will be more than 70 dB below the carrier or -83 dBm whichever is greater.

**Amplitude Blanking:**

Maximum signal output during amplitude blanking: < -85 dBm

Impulse Level in adjacent channels caused by amplitude blanking: > 22 dBm 0

**PHASE OFFSET****Range:**

$\pm 719.9^\circ$  with respect to arbitrary starting phase or assigned zero phase.

**Resolution:** 0.1°

**Increment Accuracy:**  $\pm 0.2^\circ$

**Ambient Stability:**  $\pm 1$  degree of phase per degree C.

**FREQUENCY SWEEP****Sweep Flatness:**

$\pm .15$  dB, Normal Leveling, 50 Hz to 1 MHz, .5s Sweep Time.

$\pm .15$  dB, Fast Leveling, 10 kHz to 20 MHz, .03s Sweep Time.

**Sweep Time**

**Linear Sweep:** .01 sec to 99.99 sec

**Single Log Sweep:** 2 sec to 99.99 sec

**Continuous Log Sweep:** .1 sec to 99.99 sec

**Minimum Sweep Width**

**Log Sweep:** 1 decade

**Linear Sweep:** Minimum Bandwidth (Hz) = .1 (Hz/sec) x Sweep Time (sec)

**Table 1-1. Specifications and General Information (Cont'd).****Phase Continuity:**

Sweep is phase continuous over the full frequency range

**AMPLITUDE MODULATION**

**Modulation Depth:** 0 to 100 %

**Modulation Frequency Range:** 50 Hz to 50 kHz

**Envelope Distortion:** < -30 dBc to 80% modulation

**Input Impedance:** 20 K ohm

**PHASE MODULATION**

**Range:** 0 to  $\pm 850^\circ$

**Linearity:**  $\pm .5\%$  of peak to peak deviation from best fit straight line.

**Modulation Frequency Range:** dc to 5 kHz

**Input Sensitivity:**  $\pm 5$  V peak for  $\approx 850^\circ$  phase shift ( $\approx 170^\circ/\text{volt}$ )

**Input Impedance:** 20 K ohm

**HP-IB CONTROL**

**Frequency Switching Time:** (Time to settle to within 1 Hz to final value, exclusive of programming and processing time)

< 10 ms for 100 kHz step

< 25 ms for 1 MHz step

< 70 ms for 20 MHz step

**Phase Switching Time:** (to within  $90^\circ$  of phase lock, exclusive of programming and processing time)

< 15 ms

**Amplitude Switching Time:** (to within .1 dB of final value, exclusive of programming and processing time)

< 500 ms

**AUXILIARY OUTPUTS****AUX 0 dBm:**

Frequency range is from 21 MHz to 60.999 999 999 MHz (underrange to 20.000 000 001 MHz). Amplitude is 0 dBm (50 ohm).

**SYNC OUT:**

Square wave with  $V_{\text{high}} \geq 1.2$  V,  $V_{\text{low}} \leq 0.2$  V into 50 ohms, to synchronize other instruments to the Main Signal Outputs. Level transition occurs at Main Signal Output zero crossing.

**REF OUT:**

0 dBm (50 ohm), 1 MHz signal for phase-locking additional instruments to the Model 3336.

**10 MHz OVEN OUT:**

Instruments with Option 004, only. 0 dBm (50 ohm), 10 MHz signal from a temperature stabilized, crystal oscillator for phase-locking the Model 3336 or other instruments.

**X DRIVE:**

0 to  $> +10$  Vdc linear ramp proportional to the sweep frequency. Linearity,  $\pm 1\%$  of final value, 10% to 90%, best fit straight line.

**Z BLANK:**

Sweep related TTL compatible voltage levels. Low level is capable of sinking current from a positive voltage source.

Maximum Current = 200 mA

Maximum Voltage = + 45 Vdc

Maximum Power Dissipation = 1 W

**MARKER:**

TTL compatible high to low level transition at the programmed Marker Frequency.

**Table 1-1. Specifications and General Information (Cont'd).****AUXILIARY INPUTS****EXT REF IN:**

For phase-locking the 3336A/B/C to an external frequency reference. Signal from 0 dBm to + 20 dBm (50 ohm). Signal frequency must be within  $1 \times 10^{-6}$  of a sub-harmonic of 10 MHz from 1 MHz to 10 MHz.

**AMPTD MOD:**

Amplitude modulation input (see AMPLITUDE MODULATION specifications)

**PHASE MOD:**

Phase modulation input (see PHASE MODULATION specifications)

**EXTERNAL LEVELING:**

Input from an External Leveling voltage source to regulate the signal amplitude at a remote point. Input Sensitivity: .25 dB/volt

**OPTION 004, HIGH STABILITY FREQUENCY REFERENCE****Aging Rate:**

$\pm 5 \times 10^{-8}$  per week after 72 hours continuous operation.

$\pm 1 \times 10^{-7}$  per month after 15 days continuous operation.

**Ambient Stability:**

$\pm 5 \times 10^{-8}$  maximum, 0° to 55°C

**Warm-Up Time:**

Reference frequency will be within  $1 \times 10^{-7}$  of the turn-off frequency, 20 minutes after turn-on, for an off time less than 24 hours.

**OPTION 005, HIGH ACCURACY ATTENUATOR**

Attenuation	10Hz	20 MHz
10 to 19.99 dB	$\pm .035$ dB	
20 to 39.99 dB	$\pm .06$ dB	
40 to 79.99 dB	$\pm .1$ dB	

**GENERAL****Operating Environment:**

Temperature: 0° to 55°C

Relative Humidity: 85%, 0° to 40°C

Altitude: < 15,000 ft. (< 4600 meters)

**Storage Environment:**

Temperature: -50° to +65°C

Altitude: < 50,000 ft. (< 15,000 meters)

**Power Requirements:**

100/120, 220/240 V, +5%, -10%, 48 to 66 Hz, 60 VA (100 VA with all options), 10 VA standby.

Size: 132.6 mm (5 1/4 in) high x 425.5 mm (16-3/4) wide x 497.8 (19-5/8) deep

Weight: 10 kg (22 lbs.) net, 15.5 kg (34 lbs.) shipping