



Agilent 8490D

Coaxial Attenuators

Product Overview

**dc to 50 GHz
2.4 mm connectors**



The Agilent Technologies 8490D family is a line of precision fixed coaxial attenuators with performance specified up to 50 GHz. These attenuators use the 2.4 mm coaxial connector, which exhibits excellent performance from dc to 50 GHz. The 8490D family has attenuation values of 3, 6, 10, 20, 30, and 40 dB.

The Agilent 8490D family of 2.4 mm fixed coaxial attenuators is assembled and tested with the same meticulous care as their lower frequency counterparts: the Agilent 8491, 8492, and 8493 families. These attenuators are all tested on Agilent precision analyzers to assure specifications over the full frequency range.

Applications

Ruggedness, reliability, and small size make these attenuators useful both on the bench and in systems applications. With their accuracy and low SWR they are ideally suited for extending the range of sensitive power meters for higher power measurements. The same characteristics lend themselves to applications such as calibration standards and RF substitution measurements. With their broad dc to 50 GHz frequency range and reasonable cost, general applications such as the reduction of power level to sensitive components and instrumentation systems are attractive and appropriate uses for these attenuators.

Optional test data

Use of test data is an effective means of reducing measurement uncertainty at RF and microwave frequencies. This data is available for the 8490D as Option 890. Data is generated by an automatic network analyzer and is supplied as a tabulated list of attenuation and SWR at every 400 MHz from 400 MHz to 50 GHz. Measurements are directly traceable to NIST standards, and feature very low uncertainties.



Agilent Technologies

Specifications

Options	Attenuation(dB)			SWR(Maximum)				Atten. Data Uncert. (dB)
	Min. (GHz) 0 to 50	Max. (GHz) 0 to 26.5	Max. (GHz) 26.5 to 50	(GHz) 0 to 26.5	(GHz) 26.5 to 40	(GHz) 40 to 50	(GHz) 0.4 to 50	
8490D-003	2.5	3.9	4.8	1.15	1.25	1.45	±0.6	
8490D-006	5.4	6.9	7.8	1.15	1.25	1.45	±0.6	
8490D-010	9.4	10.9	11.3	1.15	1.25	1.45	±0.6	
8490D-020	19.2	21.3	21.7	1.15	1.25	1.45	±0.6	
8490D-030	29.2	31.3	31.7	1.15	1.25	1.45	±0.8	
8490D-040	38.2	42.5	42.5	1.08	1.15	1.25	±1.7	

Specifications

Frequency range	dc to 50 GHz
Impedance (nominal)	50 Ω
Connector	2.4 mm
Power (maximum)	1 W average; 100 W peak

Environmental

Temperature	
Operating	−5°C to +50°C
Non-operating	−55°C to +75°C
Altitude	
Operating	15,000 ft
Non-operating	50,000 ft
Humidity	
Cycling, 5 days, +40°C @ 95% R.H.	8490D-003 3 dB attenuation 8490D-006 6 dB attenuation
Vibration	
0.015 in., 5-55-5 Hz, 14 min., 3 axes	8490D-010 10 dB attenuation 8490D-020 20 dB attenuation
Shock	
100 g, 1 to 2 ms, 3 times, 3 planes	8490D-030 30 dB attenuation 8490D-040 40 dB attenuation

Dimensions

Length	
27 mm (1.06 in.)	3, 6, 10, 20 dB
29 mm (1.14 in.) long	30, 40 dB
Diameter	
8 mm (.312 in.)	



Agilent Email Updates

www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.

Ordering information

Coaxial attenuator	
8490D	dc to 50 GHz, 2.4 mm coaxial connector

Options

To add options to a product, use the following ordering scheme:

Model: 8490D

Model options:

8490D-opt#1

8490D-opt#2

Attenuation (must choose one)

8490D-003	3 dB attenuation
8490D-006	6 dB attenuation
8490D-010	10 dB attenuation
8490D-020	20 dB attenuation
8490D-030	30 dB attenuation
8490D-040	40 dB attenuation

Calibration Documentation (optional)

8490D-UK6 Calibration data

Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value you receive, while minimizing your risk and problems. We strive to ensure that you get the test and measurement capabilities you paid for and obtain the support you need. Our extensive support resources and services can help you choose the right Agilent products for your applications and apply them successfully. Every instrument and system we sell has a global warranty. Support is available for at least five years beyond the production life of the product. Two concepts underlie Agilent's overall support policy: "Our Promise" and "Your Advantage."

Our Promise

Our Promise means your Agilent test and measurement equipment will meet its advertised performance and functionality. When you are choosing new equipment, we will help you with product information, including realistic performance specifications and practical recommendations from experienced test engineers. When you use Agilent equipment, we can verify that it works properly, help with product operation, and provide basic measurement assistance for the use of specified capabilities, at no extra cost upon request. Many self-help tools are available.

Your Advantage

Your Advantage means that Agilent offers a wide range of additional expert test and measurement services, which you can purchase according to your unique technical and business needs. Solve problems efficiently and gain a competitive edge by contracting with us for calibration, extra-cost upgrades, out-of-warranty repairs, and on-site education and training, as well as design, system integration, project management, and other professional engineering services. Experienced Agilent engineers and technicians worldwide can help you maximize your productivity, optimize the return on investment of your Agilent instruments and systems, and obtain dependable measurement accuracy for the life of those products.

By internet, phone, or fax, get assistance with all your test and measurement needs.

Online assistance:

www.agilent.com/find/assist

Phone or Fax

United States:	Korea:
(tel) 800 452 4844	(tel) (82 2) 2004 5004
	(fax) (82 2) 2004 5115
Canada:	
(tel) 877 894 4414	Latin America:
(fax) 905 282 6495	(tel) (305) 269 7500
	(fax) (305) 269 7599
China:	
(tel) 800 810 0189	Taiwan:
(fax) 800 820 2816	(tel) 0800 047 866
	(fax) 0800 286 331
Europe:	
(tel) (31 20) 547 2323	Other Asia Pacific Countries:
(fax) (31 20) 547 2390	(tel) (65) 6375 8100
	(fax) (65) 6836 0252
Japan:	Email:
(tel) (81) 426 56 7832	tm_asia@agilent.com
(fax) (81) 426 56 7840	

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2002

Printed in USA, May 30, 2002

5963-9931E



Agilent Technologies